

Roof and Wall Colors Roof and Wall Colors





MS Colorfast45® Paint System

29 & 26 GAUGE



Galvalume (41) Non-Painted Finish 25 Year Warranty



Galvanized (00) Non-Painted Finish No Warranty

STAR

metal sales

- * All Colors Meet or Exceed Steep Slope **ENERGY STAR® Requirements**
- † Native Copper color may vary visually based on reflection and/or installation angles

metalsales.us.com

45 Year Paint Warranty



7990 East I-25, Frontage Road Longmont, CO 80504 800.289.7663 Toll Free 303.702.5440 Phone 800.289.1617 Fax

See the back page for other finish options. All colors carry a 45 year limited paint warranty. Color selections are close representations but are limited by processing and viewing conditions. Actual samples are available by request.

PRODU	CT SOLUTION CHART		MS COLORFAST45°		ACRYLIC COATED GALVALUME®	
PANEL	PROFILE	COVERAGE	29 GA	26 GA	29 GA	26 GA
VERTICAL SEAM	Striated Flat	12"/16"/18"		•		•
MINI-BATTEN	, ,	12"/16"/18"		•		•
SOFFIT PANEL	٢٢	12"		•		•
IMAGE II™	Striated Minor Ribs	12"/16"		•		•
PRO-PANEL II®	~~~~~~	36"	•	•	•	•
CLASSIC RIB®	~	36"	•	•	•	•
PBR-PANEL		36"		•		•
IC72-PANEL		36"		•		•
7/8" CORRUGATED	~~~~~~~	Roof 32" Wall 34 ² / ₃ "		•		•
2.5" CORRUGATED	~~~~~	24"			•	•
1.25" CORRUGATED*	······	24"				•
5V-CRIMP*	~	24"			•	•
PBU-PANEL*		36"		•		•
SPAN-LINE 36A*		36"				•

Notes:

- ▶ For other colors, finishes, gauges, and materials, please inquire
- ▶ For Image II panel, refer to Image II panel brochure for color selections

PARLICT SALLITION CHART

► For panels with asterisk (*) longer lead times will apply

Legend:

- Standard colors are available in any quantity
- ◆ For standard colors, minimum quantity may be required
- Available in limited standard colors

ColorFit40[™] 40 Year Finish Warranty

Ash Grey (25) Charcoal (17) Taupe (74)

Bright White (39) Forest Green (26) White (30)

Brown (12) Light Stone (63) Zinc Grey (29)

Burnished Slate (49) Mocha Tan (22)

Burgundy (15) Red (24)

VersaRib 20 Year Finish Warranty

Bright White (39) Mocha Tan (22)
Brown (12) Ocean Blue (35)

Charcoal (17) Red (24) Forest Green (26) White (30)

Light Stone (63)

Storage Instructions

If metal roofing or siding is not going to be used immediately, it should be stored in a dry area. It should be unbundled and stood on end against an interior wall. If materials must be stored outside, protect with canvas or waterproof paper. Allow for air circulation, do not cover air-tight.

Application precautions

Avoid installing directly over green or damp lumber, porous insulation or other damaging materials. The use of a moisture barrier is recommended in such situations. Strong chemicals, such as fertilizer, manure and lime may cause damage. Storage or application near such materials should be avoided.